



Solutions for Flour and Milling

Wet Chemistry Analyses for Mills and producers of Flour

Crude Protein

OP SIS LiquidLINE has solutions for determination of Kjeldahl (TKN) protein following standard methods.

The samples are digested with sulphuric acid to convert nitrogen into ammonium sulphate. The samples are further distilled by steam distillation followed by titration.

Examples: Protein in flour, starch, starch derived products, molasses, soybean meal and other oil-seed byproducts

Our Solution

- The KjelROC Digester Advanced motor lift makes the digestion efficient and saves valuable operator time.
- OP SIS LiquidLINE Kjeldahl catalyst tablets and glass tubes ensure stable and reliable results.
- KjelROC Analyzer with integrated Titration offers titration with low relative standard deviation saving time and costs.

Standards

ISO 3188:1978
AOAC 969.37, AOAC 920.87
AOCS Ba 4b-87

Application Notes

LA1000 Application Guide Kjeldahl
LA1013 Determination of nitrogen in corn starch (maize)
Further Notes on request

Crude Fat

OP SIS LiquidLINE provides instruments to determine Crude Fat with Hot Solvent extraction.

The sample is prepared and thereafter extracted in hot solvents. Calculation of fat content follows after the extract has been dried to a constant weight.

Examples: Fat in wheat flour, corn flour and soy flour. Fat in feeds and mixed feeds.

Our Solution

- The SoxROC extraction unit with batch handling and full automation facilitates the extraction.
- The instrument provides significant time savings versus cold extraction and a recovery of over 90% of used solvents.

Standards

AOAC 922.06
AOAC 920.39
AACC 30-25

Application Notes

LA1002, Appl. Guide Solvent Extraction
Further Notes on request

Total Fat

OP SIS LiquidLINE provides instruments to determine Total Fat according to the standard methods.

The sample is hydrolysed and thereafter extracted in hot solvents. Calculation of total fat content follows after the extract has been dried to a constant weight.

Our Solution

- The HydROC hydrolysis unit offers a unique filter technology that saves time and reduces the risk of errors when moving samples between hydrolysis and extraction.
- The SoxROC extraction unit with batch handling and full automation facilitates the extraction.

Standards

-

Application Notes

LA1002, Appl. Guide Solvent Extraction
Further Notes on request