



Solutions for Oils and Syrups

Wet Chemistry Analyses for Producers of Syrups, Palm, Coconut and other Oils

Crude Protein in Oil production residues

OP SIS LiquidLINE has solutions for determination of Kjeldahl (TKN) protein following standard methods.

The samples are digested with sulphuric acid to convert nitrogen into ammonium sulphate. The samples are further distilled by steam distillation followed by titration.

Examples: Protein determination in residues from palm oil production such as palm kernel cake, palm oil sludge (POS) and palm pressed fibre (PPF). Protein in soybean meal and other oilseed by-products.

Our Solution

- The KjelROC Digestor Advanced motor lift makes the digestion efficient and saves valuable operator time.
- KjelROC Analyzer with integrated Titration offers titration with low relative standard deviation saving time and costs.

Standards

ISO 1871,
AOAC 920.176, AOAC 945.23
AOAC 984.13 , AOAC 2001.11
AOCS Ba 4b-87

Application Notes

LA1000 Application Guide Kjeldahl
Further Notes on request

Extraction of Oil

OP SIS LiquidLINE provides instruments to extract oil from plants and seeds.

The sample is prepared and thereafter extracted in hot solvents. Calculation of oil content follows after the extract has been dried to a constant weight.

Examples: Palm oil in press fiber, coconut oil in copra and oil in rape, soya beans and sunflower seeds.

Our Solution

- The SoxROC extraction unit with batch handling and full automation facilitates the extraction.
- The instrument provides significant time savings versus cold extraction and a recovery of over 90% of used solvents.

Standards

AOCS Ba 3-38
AOCS Ba 4b-87
AOAC 938.06
ISO 659

Application Notes

LA1002, Appl. Guide Solvent Extraction
LA1003, SoxROC Extraction of Palm Oil
Further Notes on request

Formaldehyde in Maple Syrup

Formaldehyde, though banned in most areas, is sometimes used to increase Maple production - causing a need to monitor for this component.

OP SIS LiquidLINE has solutions to help when determining Formaldehyde in maple syrup. Spectrophotometric measurement is used after steam distillation. OP SIS LiquidLINE instrument can be used for the distillation.

Example: Formaldehyde in Maple Syrup

Our Solution

- KjelROC Auto or Manual Distillation unit with programming capabilities make distillation easy.

Standards

AOAC 964.21 (old)

Application Notes

LA1000 Application Guide Kjeldahl
Further Notes on request